

Truck mounted Monoconductor cable Units



Single drum Monoconductor cable unit "K - 1"

Manufacturer
Gerhart - Owen

Engine Power
Torpedo, model T 4 L 912 OP3; 53 kW / 71 HP diesel, air cooled with electrical starting system

Transmission
Hydraulic engine: Sudstrand
Hydraulic pump: Sudstrand, Max. W.P. = 345 bar / 5000 PSI

Weight indicator
Hydraulic - Martin Decker 0 – 4000 lbs

Depth indicator
Mechanical – Veeder Root

Drum capacity (Monoconductor cable)
4.76 mm / 3/16" 6500 m

Dimensions
Trailer: 12.0 m (L) x 2.4 m (W) x 3.0 m (H);
Bearing capacity = 10.75 t
Cable unit: 3.9 m (L) x 2.0 m (W) x 2.0 m (H)

Safety devices
Air inlet shut off, spark arrestor, anti – static fan belts fitted

Double drum Monoconductor cable unit "K - 2"

Manufacturer
Flopetrol

Engine Power
Deutz, model F 4 L 912; 53 kW / 71 HP diesel, air cooled with electrical starting system

Transmission
Hydraulic engine: Sudstrand
Hydraulic pump: Sudstrand, Max. W.P. = 345 bar / 5000 PSI

Weight indicator
Hydraulic - Martin Decker 0 – 4000 lbs

Depth indicator
Mechanical – Veeder Root

First drum capacity
2.34 mm / 0.092" 7620 m

Second drum capacity
4.76 mm / 3/16" 6100 m

Dimensions
Cable unit: 3.5 m (L) x 1.8 m (W) x 2.2 m (H)
Vehicle: MAN TGA 18.320 4x2 BL

Safety devices
Air inlet shut off, spark arrestor, anti – static fan belts fitted