



# Truck mounted crane Slickline units - 3 pcs

## Manufacturer

Maritime Hydraulics

## Truck

International, 2674 Series

## Engine Power

Cummins, model N14+; 295 kW / 395 HP diesel, air cooled with electric starting system

## Hydraulic system

Hydraulic pump: Sauer Sundstrand, model series 90L100; capacity 200 l/min at 2200 RPM

Hydraulic engine: Sauer Sundstrand, model series 90M100 6.1"; Max. pressure 345 bar / 5000 lbs

Control valve: Sauer Sundstrand, model MCH / EDC

## Weight indicator

Hydraulic - Martin Decker 0 – 2000 lbs

Electronic – RS Corporation 0 – 999999 lbs

## Depth indicator

Mechanical – Maritime Hydraulics 0 – 999999 m

Electronic – RS Corporation 0 – 999999 m

## First drum capacity

2.74 mm / 0.108" 6100 m / 20 000 ft

## Second drum capacity

3.17 mm / 0.125" 6100 m / 20 000 ft

## Crane

Manufacturer: National Crane

Series: 600C

Capacity: certified for 5 t

Extended length: 22.25 m

Maximum lift radius: 20 m

## Wireline Recorder

Manufacturer - Reliable Scale Corporation; Data recorded – weight, line speed, depth, time & date

## BOP and Stuffing Box Control Panel

Max. W.P. – 210 bars / 3000 PSI; Placed in operator's cab for easy access

Air inlet shut off, spark arrestor, anti – static fan belts fitted

## Dimensions

11.1 m (L) x 2.5 m (W) x 4.1 m (H); Weight = 22.5 t

