



INTEGRATED DRILLING & WELL SERVICES Co., Ltd,
A MEMBER OF THE **INA** GROUP

SKYTOP 1

Skytop Brewster RR 750
2 x 235 kW Mobile Workover/Drilling Rig

DEPTH RANGE:

2500 m with 5" D.R 3200 m with 3 1/2" D.R

MAST:

Skytop-Brewster 112-300XF, 34 m (136 t)

SUBSTRUCTURE:

Height: 5.18 (17 ft)

Clearance to the beams: 4.1 m (13.6 ft)

CROWN BLOCK:

Skytop-Brewster

Grooved: 1"

Capacity: 136 t

TRAVELLING BLOCK & HOOK:

Skytop-Brewster HB 245

Capacity: 150 t

SWIVEL:

IDECO TL 200

Capacity: 200 t

DRAWWORKS:

Skytop Brewster RR 750 powered by two DD 8V71 engines,
235 kW each

ROTARY TABLE:

Continental - Emsco T 2750

Capacity: 454 mt; Skytop 180 RSH – 300t

POWER PLANT:

CAT398, AC, Uljanik, 750 kVA

G.M. 6A71N, 135 kVA

Mud Pumps:

two WIRTH DUPLEX 1000 HP powered by CAT 399/398

one NATIONAL JWS-400 TRIPLEX powered by

G.M. 12 V-71N

Mud Tanks:

Mud Tanks: 6 x 35 m³

Water Tanks: 4 x 50 m³

Chemical Tank: 2 x 20 m³



SOLIDS CONTROL:

Mud Cleaner: Lendava Brandt

Shale Shaker: Lendava Brandt

MUD/GAS SEPARATORS:

Mud/ Gas Separator: SWACO - Vacuum

APOLLO-Atmospheric
