



NATIONAL 801

3000 HP Drilling Rig

RATED DRILLING DEPTH:

8000 m with 5" D.P

SUBSTRUCTURE:

Height: 11.28 m (37 ft)

Height under rotary beams: 9.14 m (30 ft)

Set Back: 363 mt

MAST:

Pyramid 48.77 m (160 ft)

Capacity: 680 mt

CROWN BLOCK:

No of sheaves: 2+1

Grooved: 1 1/2"

Capacity: 680 mt

TRAVELLING BLOCK & HOOK:

Oilwell A-750 & BJ 5750

Capacity: 680 mt

SWIVEL:

National P 650

Capacity: 590 mt

TOP DRIVE:

VarcoTDS-3

Capacity: 450 mt


DRAWWORKS:

National 1625 UDBE, 3 x GE 752 R, 750 kW each

ROTARY TABLE:

National C-495, 49 1/2"

Capacity: 726 m



POWER PLANT:

Diesel Engines: 3 x Cat 3516 STD, 1350 kW each + 1 x Cat 3512

Generators: AC, 4 x Cat SR-4, 1900 kVA each

CONVERSION SYSTEM:

General Electric AC-DC Microdrill 3000

No of SCRs: 8

MUD SYSTEM:

Mud Pumps: 3 x National 12-P-160, each pump powered by 2 x GE 752 R, 660 kW each

Mud Tanks: 7+1, Total capacity: 430 m³

Water Tanks: 1, Total capacity: 60 m³

Shale Shaker: Derrick Flo-Cleaner 58 + Swaco Mongoose x 2

Mud Cleaner: Brandt Double Dual Tandem

Desanden Pioneer T 2x12"

Desilten Pioneer T 18x4"

Mud/Gas Separator Atmospheric

Degassen Brandt, Vacuum DG-10