

# Trailer mounted Monoconductor cable Units



## Single drum Monoconductor cable unit "K - 1"

**Manufacturer**  
Gerhart - Owen

**Engine Power**  
Torpedo, model T 4 L 912 OP3; 53 kW / 71 HP diesel, air cooled with electrical starting system

**Transmission**  
Hydraulic engine : Sudstrand  
Hydraulic pump : Sudstrand, Max. W.P. = 345 bar / 5000 PSI

**Weight indicator**  
Hydraulic - Martin Decker 0 – 4000 lbs

**Depth indicator**  
Mechanical – Veeder Root

**Drum capacity ( Monoconductor cable )**  
4.76 mm / 3/16 " 6500 m

**Dimensions**  
Trailer : 12.0 m (L) x 2.4 m (W) x 3.0 m (H);  
Bearing capacity = 10.75 t  
Cable unit : 3.9 m (L) x 2.0 m (W) x 2.0 m (H)

**Safety devices**  
Air inlet shut off, spark arrestor, anti – static fan belts fitted

## Double drum Monoconductor cable unit "K - 2 "

**Manufacturer**  
Flopetrol

**Engine Power**  
Deutz, model F 4 L 912; 53 kW / 71 HP diesel, air cooled with electrical starting system

**Transmission**  
Hydraulic engine : Sudstrand  
Hydraulic pump : Sudstrand, Max. W.P. = 345 bar / 5000 PSI

**Weight indicator**  
Hydraulic - Martin Decker 0 – 4000 lbs

**Depth indicator**  
Mechanical – Veeder Root

**First drum capacity**  
2.34 mm / 0.092" 7620 m

**Second drum capacity**  
4.76 mm / 3/16 " 6100 m

**Dimensions**  
Trailer : 12.0 m (L) x 2.4 m (W) x 3.0 m (H);  
Bearing capacity = 10.75 t  
Cable unit : 3.5 m (L) x 1.8 m (W) x 2.2 m (H)

**Safety devices**  
Air inlet shut off, spark arrestor, anti – static fan belts fitted