

FINANCE & CORPORATE SERVICES

CORPORATE SERVICES

Ulica grada Vukovara 18
10000 Zagreb, Croatia
Tel: +385 1 3652 333
N-12/10/2020/SH

Zagreb, 28.11.2020

Subject: SALE OF DRILLING RIG Emsco-602

Subject of sale: Drilling Rig Emsco-602 (see attached short description)

Note: all spare parts that are currently available on rig site are included

Ownership: 100% owned by CROSCO, Integrated well services, Ltd.

Location of the rig: Borg El-Arab,
Alexandria, Egypt
[Location map](#)

Contact at location: Oliver Horvatić, Phone: +38598277706
e-mail: Oliver.Horvatic@ina.hr

Contact for technical issues: Bruno Hudi, Phone: +385912771801
e-mail: bruno.hudi@croscos.hr

The parity: Ex works, current location.

Delivery of Commercial offer to: sale-equip@croscos.hr

Offer due date: December 31st 2020.

Organization and costs of transport and all other related expenses are buyer's obligation.

Additional technical documentation and clarification could be provided on request.

Corporate Services Manager


Marko Glamuzina

Company Director


Igor Kruljac



www.croscos.com

CROSCO, naftni servisi, d.o.o. – CROSCO, Integrated Drilling & Well Services Company, Ltd.

Adresa - Address Ulica grada Vukovara 18, 10000 Zagreb, Hrvatska - Croatia **Telefon - Phone:** +385/1/36 52 333 **Fax:** +385/1/30 96 448

Banka - Bank

Privredna banka Zagreb d.d.
Raiffeisenbank Austria d.d.
OTP banka d.d.

IBAN

HR8623400091100139701
HR1424840081100564134
HR8724070001100567956

Adresa – Address

Radnička 50, 10000 Zagreb
Petrinjska 59, 10000 Zagreb
Domovinskog rata 61, 21000 Split

Trgovački sud u Zagrebu - Commercial Court

MBS: 080114508
Temeljni kapital - Capital stock
581.982.400,00 kn
Uplaćen u cijelosti - Paid up
Matični broj - Ident. No. 1245449
OIB: 15538072333

Direktor Društva – Company Director: Igor Kruljac





EMSCO 602

2000 HP Drilling Rig

RATED DRILLING DEPTH:

6000 m with 5" D.P.

SUBSTRUCTURE:

Height: 7.92 m (26 ft)
Height under rotary beams: 5.79 m (19 ft)
Set Back: 272 mt

MAST:

Pyramid 43.28 m (142 ft)
Capacity: 454 mt

CROWN BLOCK:

No of sheaves: 7
Grooved: 1 3/8"
Capacity: 454 mt

TRAVELLING BLOCK & HOOK:

Emsco RA-52-6 & BJ 5500
Capacity: 500 mt

SWIVEL:

National/Oilwell PC 500
Capacity: 500 mt

DRAWWORKS:

Emsco C-2 II 2000 HP, 2 x DC 5 GE-752 R, 750 kW each

TOP DRIVE:

Aker Kvaerner PTD 500 AC
Capacity: 454 mt

ROTARY TABLE:

Emsco T-2750, 27 1/2"
Capacity: 454 mt



POWER PLANT:

Diesel Engines: 4 x Cat D 3512; 2 x Olympian Geh 250, total output power: 6000kW
Generators: 4 x Cat SR-4, 1500 kVA each; Olympian Geh 250, 2 x 230

CONVERSION SYSTEM:

SCR, HELB
No of SCRs: 9

MUD SYSTEM:

Mud Pumps: 3 x Emsco FB 1600, each pump powered by 2 x DC 5 GE 752 R, 750 kW each
Mud Tanks: 6, Total capacity: 525 m³
Water Tanks: 2, Total capacity: 160 m³
Shale Shaker: 2 x Brandt King Cobra Single type
Mud Cleaner: Brandt Dual Tandem
Desander: Swaco T 2 x 12
Desilter: Swaco T 16 x 4"
Mud/Gas Separator: Atmospheric
Degasser: Swaco, Vacuum